

MK 25 MOD 2 UBA POSTDIVE CHECKLIST		
For use of this form, see FM 3-05.212; the proponent agency is TRADOC.		
DIVER NAME	DATE (YYYYMMDD)	RIG #
<p><b>NOTE 1:</b> Refer to MRC for detailed step-by-step procedures.</p> <p><b>NOTE 2:</b> For repetitive dives using the same LAR V rig, a complete postdive need only be performed at the end of the dive day, provided cumulative time of dive does not exceed canister duration limits.</p>		
INITIALS		
	1. Ensure dive surface valve is in the surface (closed) position.	
	2. Secure the system and remove apparatus from diver.	
	3. Rinse the rig in fresh water.	
	4. Record oxygen bottle pressure: _____ BAR.	
	5. Close supply valve and vent pneumatic system.	
	6. Remove oxygen bottle and insert protective plug in regulator. Place protective cap on supply valve and place in rack.	
	7. Remove retainer strap from canister.	
	8. Disconnect breathing bag from demand valve.	
	9. Disconnect mouthpiece and hoses.	
	10. Disconnect breathing bag from scrubber canister.	
	11. Rinse mouthpiece, hoses, and breathing bag in fresh water; remove excess water; and hang components to dry.	
	12. Empty, clean, and dry scrubber canister.	
	13. Ensure automatic demand valve is completely dry.	
	14. Store equipment in proper condition and place, with dive surface in open position.	
REMARKS		
POSTDIVE COMPLETION TIME	DIVER SIGNATURE	DIVING SUPERVISOR SIGNATURE